

LA-CO Industries, Inc.

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Date of issue: 04/22/2015

Revision date: 01/07/2019

Supersedes: 07/11/2018

Version: 4.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Temperature indicator
Restrictions on use : No additional information available

1.3. Supplier

LA-CO Industries, Inc.
1201 Pratt Boulevard
Elk Grove Village, IL. 60007-5746
Phone: (847) 956-7600
Fax: (847) 956-9885
E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification
Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labelling
No labelling applicable

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

181.48% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
260.18% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
260.18% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Concentration ranges are due to batch differences.

Name	Product identifier	%	GHS-US classification
2',4'-dimethylacetoacetanilide	(CAS-No.) 97-36-9	0 - 85	Acute Tox. 4 (Oral), H302
adipic acid	(CAS-No.) 124-04-9	0 - 7	Eye Irrit. 2A, H319
salicylamide	(CAS-No.) 65-45-2	0 - 9	Acute Tox. 4 (Oral), H302
Iron oxide red	(CAS-No.) 1309-37-1	0 - 2	Aquatic Chronic 2, H411
butyl 4-hydroxybenzoate	(CAS-No.) 94-26-8	0 - 1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
phenyl salicylate	(CAS-No.) 118-55-8	0 - 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
lithium sulphate	(CAS-No.) 10377-48-7	0 - 5	Acute Tox. 4 (Oral), H302

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash with plenty of water/....

First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.

First-aid measures after ingestion : Rinse mouth. Call a POISON CENTER/doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand.

Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

Fire hazard : No specific fire or explosion hazard. Burning produces irritating, toxic and noxious fumes.

Reactivity : No dangerous reactions known.

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing. EN469.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable gloves.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Wear suitable gloves.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

- Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Avoid generating dust. Contain and collect as any solid.
- Methods for cleaning up : Minimise generation of dust. On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

- Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed.
- Incompatible products : Strong oxidizers. Strong bases.
- Prohibitions on mixed storage : Keep away from incompatible materials.
- Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

phenyl salicylate (118-55-8)

Not applicable

butyl 4-hydroxybenzoate (94-26-8)

Not applicable

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

2',4'-dimethylacetoacetanilide (97-36-9)

Not applicable

salicylamide (65-45-2)

Not applicable

Iron oxide red (1309-37-1)

OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³

adipic acid (124-04-9)

ACGIH	Local name	Adipic acid
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	Remark (ACGIH)	URT irr; ANS impair

lithium sulphate (10377-48-7)

Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear dust impervious gloves. EN374

Eye protection:

EN166. In case of dust production: protective goggles

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges. EN 12083

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable
Odour	: odourless
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Keep away from incompatible materials. Avoid creating or spreading dust.

10.5. Incompatible materials

Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Unknown acute toxicity (GHS US)	181.48% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 260.18% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 260.18% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
---------------------------------	---

phenyl salicylate (118-55-8)

LD50 oral rat	3000 mg/kg
ATE US (oral)	3000 mg/kg bodyweight

butyl 4-hydroxybenzoate (94-26-8)

LD50 oral rat	13200 mg/kg
ATE US (oral)	13200 mg/kg bodyweight

2',4'-dimethylacetoacetanilide (97-36-9)

LD50 oral rat	1995 mg/kg
ATE US (oral)	1995 mg/kg bodyweight

salicylamide (65-45-2)

LD50 oral rat	1400 mg/kg
ATE US (oral)	1400 mg/kg bodyweight

Iron oxide red (1309-37-1)

LD50 oral rat	> 10000 mg/kg
LD50 dermal rat	5500 mg/kg
LC50 inhalation rat (mg/l)	5.05 mg/l/4h
ATE US (dermal)	5500 mg/kg bodyweight
ATE US (vapours)	5.05 mg/l/4h
ATE US (dust,mist)	5.05 mg/l/4h

adipic acid (124-04-9)

LD50 oral rat	5560 mg/kg
LD50 dermal rabbit	7940 ml/kg
LC50 inhalation rat (mg/l)	> 7.7 mg/l/4h
ATE US (oral)	5560 mg/kg bodyweight

lithium sulphate (10377-48-7)

LD50 oral rat	613 mg/kg
ATE US (oral)	613 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.

Iron oxide red (1309-37-1)

IARC group	3 - Not classifiable
------------	----------------------

lithium sulphate (10377-48-7)

NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight
---	---------------------

Reproductive toxicity	: Not classified
-----------------------	------------------

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

STOT-single exposure : Not classified

phenyl salicylate (118-55-8)	
STOT-single exposure	May cause respiratory irritation.
butyl 4-hydroxybenzoate (94-26-8)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

adipic acid (124-04-9)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight/day

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Likely routes of exposure : Inhalation. Skin and eye contact.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

SECTION 12: Ecological information

12.1. Toxicity

2',4'-dimethylacetoacetanilide (97-36-9)	
LC50 fish 1	250 (250 - 350) mg/l
salicylamide (65-45-2)	
LC50 fish 1	101 mg/l 96 h
EC50 Daphnia 1	75 mg/l 24 h
Iron oxide red (1309-37-1)	
EC50 Daphnia 1	> 100 mg/l
adipic acid (124-04-9)	
LC50 fish 1	>= 1000 mg/l 96 h
EC50 Daphnia 1	46 mg/l 48 h
lithium sulphate (10377-48-7)	
LC50 fish 1	30.3 mg/l read-across, 96 h
EC50 Daphnia 1	33.2 mg/l read across, 48 h
LOEC (chronic)	24.35 mg/l read-across lithium hydroxide monohydrate
NOEC (chronic)	17.35 mg/l read-across lithium hydroxide monohydrate

12.2. Persistence and degradability

phenyl salicylate (118-55-8)	
Persistence and degradability	Moderately biodegradable.
2',4'-dimethylacetoacetanilide (97-36-9)	
Biodegradation	25 % 28 d

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

salicylamide (65-45-2)	
Biodegradation	99 % 28 d
adipic acid (124-04-9)	
Persistence and degradability	Readily biodegradable.
Biodegradation	90 % 5 d

12.3. Bioaccumulative potential

phenyl salicylate (118-55-8)	
Log Pow	3.82
Bioaccumulative potential	Not established.
2',4'-dimethylacetoacetanilide (97-36-9)	
Log Pow	1.4
salicylamide (65-45-2)	
Log Pow	1.31
adipic acid (124-04-9)	
BCF fish 1	3.162
Log Pow	0.093
lithium sulphate (10377-48-7)	
Log Pow	-4.38

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transportation of Dangerous Goods

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Aluminum oxide	CAS-No. 1344-28-1	0 - 0.5%
----------------	-------------------	----------

adipic acid (124-04-9)

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

CANADA

phenyl salicylate (118-55-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

butyl 4-hydroxybenzoate (94-26-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2',4'-dimethylacetoacetanilide (97-36-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

salicylamide (65-45-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Iron oxide red (1309-37-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

adipic acid (124-04-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

lithium sulphate (10377-48-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

phenyl salicylate (118-55-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

butyl 4-hydroxybenzoate (94-26-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

2',4'-dimethylacetoacetanilide (97-36-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

salicylamide (65-45-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Iron oxide red (1309-37-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

adipic acid (124-04-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

lithium sulphate (10377-48-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).
All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

phenyl salicylate (118-55-8)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on Taiwan National Chemical Inventory
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)

butyl 4-hydroxybenzoate (94-26-8)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on Taiwan National Chemical Inventory
Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

2',4'-dimethylacetoacetanilide (97-36-9)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on Taiwan National Chemical Inventory
 Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Korean ECL (Existing Chemicals List)

salicylamide (65-45-2)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on Taiwan National Chemical Inventory
 Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Korean ECL (Existing Chemicals List)

Iron oxide red (1309-37-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on KECI (Korean Existing Chemicals Inventory)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on Taiwan National Chemical Inventory
 Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

adipic acid (124-04-9)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on Taiwan National Chemical Inventory
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).

lithium sulphate (10377-48-7)

Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

⚠ WARNING: This product can expose you to 1-[(2,4-dinitrophenyl)azo]-2-naphthol C.I. Pigment Orange 5, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
1-[(2,4-dinitrophenyl)azo]-2-naphthol C.I. Pigment Orange 5(3468-63-1)	X					

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Silicon dioxide (cristobalite)(14808-60-7)	X					
Carbon black(1333-86-4)	X					

Component	State or local regulations
Iron oxide red(1309-37-1)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
adipic acid(124-04-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 01/07/2019

Data sources : ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:


Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 525 °F (274 °C), 554 °F (290 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weighted Average
	TSCA: Toxic Substances Control Act

- NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
- NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:
Added. Product.

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product